

UNION

UNION RUPTURE DISC HOLDER

The Oseco Union Rupture Disc Holder is economical and ideal for applications where installation space is limited. Installation time is reduced, as only the union nut is removed to obtain access to the rupture disc.

The Union Rupture Disc Holder has a 30° angular seat arrangement and is for use with the STD series and CO series rupture discs.



Oseco's Union Holder is excellent for applications where space is limited.

- NPT threads are standard, other connections available upon request
- Standard materials of construction are Carbon Steel and 316 Stainless Steel.
- Designed to meet ASME standards

Sizes

1/2", 1", 1 1/2" and 2"

Common Applications

Applications with limited space



Related Products

RUPTURE DISCS
CO
STD

Oseco Union Holder Technical Specifications

Rating for Carbon Steel Union Rupture Disc Holders

SERVICE TEMPERATURE ° F	NOMINAL RATINGS (psig)		
	1,200 CLASS	3,000 CLASS	6,000 CLASS
100	1,200	3,000	6,000
150	1,180	2,950	5,919
200	1,160	2,900	5,830
250	1,140	2,850	5,750
300	1,120	2,800	5,690
350	1,095	2,740	5,625
400	1,075	2,690	5,550
450	1,050	2,630	5,490
500	1,000	2,500	5,210
550	950	2,370	4,925
600	890	2,220	4,620
650	830	2,070	4,300
700	760	1,900	3,920
750	680	1,700	3,550
850	490	1,230	2,500
900	420	1,050	1,750
950	330	825	1,375
1,000	240	600	1,000

Certifications

ASME UD

Let us help you with all
your pressure relief questions.
Call us at **(800) 395-3475**
or email us at info@oseco.com.

www.oseco.com

